

SECONDARY CONTAINMENT BERMS

L-ROD

PROTECT YOUR SITE FROM CONTAMINATION, LEAKS AND SPILLS.

Appropriate for larger areas to keep your worksite safe, clean and within regulations by containing leaks and spills with an inexpensive, portable environmental safeguard.






Norseman's L-Rod Secondary Containment Berms are appropriate when secondary containment of wastewater, petroleum products and various chemicals are required. Place our L-Rod Secondary Containment Berms under larger equipment and vehicles to protect the ground from leaks and spills. They can be used in multiple applications, such as on a worksite, under machinery or during a plant shutdown.

In stock, ready to ship from one of our distribution locations.

Norseman's L-Rod Secondary Containment Berms are **GEAR2PERFORM**.

GEAR POINTS:

Outwork. Outperform. Overachieve.

-  Prevent ground contamination from leaks and spills of hydrocarbons, chemicals or other potentially environmentally damaging materials.
-  Multiple Hyprene™ fabric types are available to offer the right combination of protection and value for any project. Berms are supported with 12" metal L-shaped flat bar brackets.
-  Water-resistant, chemical resistant and hydrocarbon resistant.
-  In-stock, ready-to-order products and custom configurations available.
-  Quick and easy setup; collapsible for easy transport and compact storage.



MADE IN CANADA

**GEAR2
PERFORM**

CANADA 1.800.268.1918 NORSEMAN.CA

USA 1.844.667.7362 NORSEMANUSA.COM



SECONDARY CONTAINMENT BERMS

L-ROD





FEATURES

- Tested welds help ensure maximum performance.
- Berm walls are supported with 12" galvanized-metal L-shaped flat bar brackets.
- Available in four fabric options:
 1. Hyprene™ XC (yellow) – Best for water, oil and cold temperatures; rated to –67°F (–55°C).
 2. Hyprene CR (orange) – Best for chemicals, fuel and acids; rated to –13°F (–25°C).
 3. Hyprene ST (multiple colors) – Good for water and oil; rated to –49°F (–45°C).
 4. Hyprene XR-5 (black) – Best for chemicals, fuel and abrasion resistance; rated to –22°F (–30°C).
- Quick and easy setup.
- Collapsible for easy transport and compact storage.
- Available in stock with Hyprene XC fabric and 12" L-bracket configuration in sizes from 8' x 8' to 12' x 12'.
- Custom fabric options and size configurations available to meet specific containment requirements.

GEAR INFORMATION:

PRODUCT	ITEM NUMBER	COLD CRACK	SIZE	WALL	AVAILABILITY
Hyprene™ XC	412246	–67°F (–55°C)	8' x 8'	12" L-Bracket	In Stock
Hyprene XC	412447	–67°F (–55°C)	10' x 10'	12" L-Bracket	In Stock
Hyprene XC	412248	–67°F (–55°C)	12' x 12'	12" L-Bracket	In Stock
Hyprene XR-5	450420	–22°F (–30°C)	8' x 8'	12" L-Bracket	Made to Order
Hyprene XR-5	450421	–22°F (–30°C)	10' x 10'	12" L-Bracket	Made to Order
Hyprene XR-5	450422	–22°F (–30°C)	12' x 12'	12" L-Bracket	Made to Order

NORSEMAN, YOUR ONE-STOP SUPPLIER OF GEAR2PERFORM.

-  **On-Demand Supply:** Warehousing space and distribution locations across North America.
-  **Exceptional Service:** One-stop supplier of Fabric, Foam and Film Protective solutions.
-  **Superior Quality:** Manufacturing in North America since 1921.
-  **Extensive Experience:** Our Fiercely Reliable™ team will find a solution to fit your business.

Contact Norseman or your local Sales Representative to order today.

To learn more about Norseman and our gear, contact one of your local Norseman Sales Representatives or visit our website.

CANADA 1.800.268.1918 NORSEMAN.CA
USA 1.844.667.7362 NORSEMANUSA.COM

