



# AERO AIRSTREAM™ INSULATED

## INSULATED A/C VENTILATION DUCT. BRIGHTER. COOLER. STRONGER.

Norseman's Insulated Aero Airstream operates in both high and low temperatures. It's manufactured with tear-resistant fabrics and unique features for maximum durability and efficiency—ideal for construction and industrial environments, large tents, temporary structures and more.

### ⚙️ SPECIFICATIONS:

- Manufactured with fire-retardant (FR) insulated Polyethylene (PE) fabric; water, mold/mildew and fire resistant, and odor-free.
- Insulation maintains temperature of air inside the hose.
- Puncture damage and tearing are limited through high tensile strength, ensuring performance isn't compromised.
- FR polyvinyl chloride (PVC) wear strip provides an additional layer of protection.
- Standard colors: White with white wear strip.
- UV-resistant chrome finish ensures a bright-white, no-fade professional look, even after extensive use.
- Wire helix provides a strong structure, ensuring consistent airflow in both horizontal and vertical applications.
- PE fabric's smooth interior provides maximum airflow with minimal friction loss, delivering the full volume of air to where you need it.
- Sewn-in grommet tabs allow for easy overhead suspension.
- Integrated compression straps assist with carrying and ensure compact storage.
- Passes FR testing to NFPA 701 and CAN/ULC-S109 standards.



## **NORSEMAN, YOUR ONE-STOP SUPPLIER OF GEAR2PERFORM.**

- 📍 **On-Demand Supply:** Warehousing space and distribution locations across North America.
- 🤝 **Exceptional Service:** One-stop supplier of Fabric, Foam and Film Protective solutions.
- ⚙️ **Superior Quality:** Manufacturing in North America since 1921.
- 💡 **Extensive Experience:** Our Fiercely Reliable™ team will find a solution to fit your business.

Contact Norseman or your local Sales Representative to order today.



# AERO AIRSTREAM™

# INSULATED

**GEAR POINTS:** Features specifically designed to ensure Norseman Gear outperforms on your next jobsite.

Direct cooled air into your environment.



**PROTECT**

FR insulated Polyethylene with FR PVC wear strip.



**WITHSTAND**

Horizontal or vertical airflow.



**FIT**

Quick-connect collar configurations provide a secure connection.



**PERFORM**



## **CONNECTION:**

- Standard coil pitch: Supply, 6"; return, 4".
- Available in multiple collar configurations for different connections—wire-ring, belted-cuff, or gear-clamp—allowing for easy installation.

## **STANDARD SIZING:**

- 12" x 25'
- 16" x 25'
- 20" x 25'

## **TEMPERATURE RATING:**

−22°F to 200°F (−30°C to 93°C)

## **CUSTOMIZATION:**

*Custom Options Available*

ITEM NUMBER	COLLAR CONFIGURATION	DIAMETER	LENGTH
450964	Belted-Cuff Collars (Both Ends)	12"	25'
450965	Belted-Cuff Collars (Both Ends)	16"	25'
451156	Wire-Ring Collars (Both Ends)	16"	25'
450966	Belted-Cuff Collars (Both Ends)	20"	25'
451087	Belted-Cuff / Wire-Ring Collars	20"	25'

To learn more about Norseman and our gear, contact one of your local Norseman Sales Representatives or visit our website.

**CANADA 1.800.268.1918 NORSEMAN.CA**  
**USA 1.844.667.7362 NORSEMANUSA.COM**