



NEW & ENHANCED FOREMAN[®] 500 Indirect-Fired Portable Heater

- ✓ **Reliable BTU** at 500,000 btu/hr
- ✓ **Reliable CFM** with two 12" dia. outlet
- ✓ **One-person portability** with handle and wheels
- ✓ **Quiet operation** at 70 dB or less
- ✓ **NEW Operator-friendly control panel** with:
 - Voltmeter that monitors incoming volts
 - Hour meter that clocks actual runtime (heat mode only)
 - Status and diagnostic lights
- ✓ **NEW 57-gal. fuel tank** for 15-gal of added capacity and +5 to 6 hours of max runtime (oil model only)
- ✓ **Loaded with options to aid fuel efficiency** including thermostatic control, recirculation mode, and fan-only vent mode
- ✓ **Jobsite tough** with indoor/outdoor rating, robust parts and protective frame
- ✓ **Efficient storage options** with no flat wheels and frame that allows for vertical stacking

L.B. WHITE LINK L.B. White LINK[™]
Now telematics-enabled to put critical alerts, runtime, location, and more at your fingertips.
Learn more at LBWhite.com/LINK.

- Accessories (Sold Separately)**
- Vent Pipe Extension
 - Rain Cap
 - Regulator for DF model only
 - Gas Hose for DF model only
 - Duct (12", 16" and/or 20" dia.)
 - Duct Adapter (Takes 2 x 12" down to 1 x 16")
 - Thermostat with 25 ft cord
 - Beckette[®] GeniSys Contractor Display Tool (For oil model only)
 - Stacking Kit



Two 12" dia. duct up to 100 ft.



One 16" dia. duct up to 100 ft. using duct adapter (sold separately)



One-person portability



NEW Control Panel:

- Volt Meter
- Hour Meter
- Diagnostic Lights



Air recirculation option, 20" dia. duct runs up to 25 ft.



Stackable (kit sold separately)



NEW & ENHANCED

FOREMAN[®] 500

Indirect-Fired Portable Heater



FOREMAN [®]		500 DF	500 OIL
BTU/H RATING		500,000	500,000
FUEL TYPE		LP, NG	DIESEL
FUEL CONSUMPTION MAX	LP (LBS./HR)	23.0	--
	NG (CU.FT/HR)	500.0	--
	DIESEL 1 OR 2 (G/HR)	--	3.6
INLET GAS PRESSURE MIN./MAX.	LP (IN W.C.)	8/13.5	--
	NG (IN W.C.)	8/13.5	--
BURNER TYPE		RIELLO [®]	BECKETT [®]
TANK CAPACITY (GALLON)		--	57
BLOWER FAN OUTPUT (CFM)		3,457	3,457
OUTLET STATIC PRESSURE (IN W.C.)		2.5	2.5
OUTLET DUCT DIAMETER (INCH)		12X2	12X2
RECIRCULATION DUCT DIAMETER (INCH)		20	20
MOTOR HORSEPOWER		1.5	1.5
ELECTRICAL SUPPLY (VOLTS/HZ/PHASE)		120/60/1	120/60/1
RUNNING AMPS		13.5	13.5
UNIT WEIGHT (LBS)		829	979
UNIT LENGTH (IN)		94.0	94.0
UNIT WIDTH (IN)		32.0	32.0
UNIT HEIGHT (IN)		53.0	53.0
SHIP WEIGHT (LBS)*		850.0	1000.0
SHIP LENGTH (IN)		101	101
SHIP WIDTH (IN)		39	39
SHIP HEIGHT (IN)		60	60
LINK [™] CAPABLE		S	S
LINK [™] READY		0	0
THIRD PARTY CERTIFIED TO ANSIZ83.7/CSA 2.14-2017		YES	YES



TWO YEAR WARRANTY



S=Standard O=Optional

*Ships on custom pallet.

Heaters ship standard to run at 0-2000 feet.
To operate at higher altitudes, please note in order process to allow for appropriate deviation.

CA RESIDENTS:
 **WARNING**
 Cancer and reproductive harm. See www.P65Warnings.ca.gov.

INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650
 (800) 345 7200
 (608) 783 5691
 (608) 783 6115, fax
www.lbwhite.com

 MADE IN USA
 OF U.S. & IMPORTED PARTS

© 2021 L.B. White Co.
 All rights reserved.
 All specifications are subject to change without notice.