

AERO AIRSTREAM™

OUR SIGNATURE VENTILATION DUCT. BRIGHTER. COOLER. STRONGER.

Norseman's Aero Airstream is our signature A/C and ventilation duct. It's manufactured with tear-resistant fabrics and unique features for maximum durability and efficiency—ideal for construction and industrial environments, large tents, temporary structures and more.

SPECIFICATIONS:





- Manufactured with fire-retardant (FR) Polyethylene (PE) fabric; water, mold/mildew and fire resistant, and odor-free.
- Puncture damage and tearing are limited through high tensile strength, ensuring performance isn't compromised.
- FR polyvinyl chloride (PVC) wear strip provides an additional layer of protection.
- Standard colors: White with white wear strip.
- UV-resistant chrome finish ensures a bright-white, no-fade professional look, even after extensive use.
- Wire helix provides a strong structure, ensuring consistent airflow in both horizontal and vertical applications.
- PE fabric's smooth interior provides maximum airflow with minimal friction loss, delivering the full volume of air to where you need it.
- Sewn-in grommet tabs allow for easy overhead suspension.
- Integrated compression straps assist with carrying and ensure compact storage.
- Passes FR testing to NFPA 701 and CAN/ULC-S109 standards.



In stock, ready to ship from one of our distribution locations.

Norseman's Aero Airstream A/C & ventilation duct is **GEAR2PERFORM**.

NORSEMAN, YOUR ONE-STOP SUPPLIER OF **GEAR2PERFORM**.

-  **On-Demand Supply:** Warehousing space and distribution locations across North America.
-  **Exceptional Service:** One-stop supplier of Fabric, Foam and Film Protective solutions.
-  **Superior Quality:** Manufacturing in North America since 1921.
-  **Extensive Experience:** Our Fiercely Reliable™ team will find a solution to fit your business.

Contact Norseman or your local Sales Representative to order today.



GEAR POINTS: Features specifically designed to ensure Norseman Gear outperforms on your next jobsite.

Direct cooled air into your environment.



PROTECT

FR Polyethylene with FR PVC wear strip.



WITHSTAND

Horizontal or vertical airflow.



FIT

Quick-connect collar configurations provide a secure connection.



PERFORM



 **CONNECTION:**

- Standard coil pitch: Supply, 6"; return, 4".
- Available in multiple collar configurations for different connections—wire-ring, belted-cuff, or gear-clamp—allowing for easy installation.

 **STANDARD SIZING:**

- 12" x 25'
- 14" x 25'
- 16" x 25'
- 18" x 25'
- 20" x 25'
- 24" x 25'

 **TEMPERATURE RATING:**

-22°F to 200°F (-30°C to 93°C)

 **CUSTOMIZATION:**

Custom Options Available

ITEM NUMBER	COLLAR CONFIGURATION	DIAMETER	LENGTH
450948	Pin-Lock / Belted-Cuff Collars	12"	25'
413335	Wire-Ring Collars (Both Ends)	12"	25'
413336	Wire-Ring Collars (Both Ends)	16"	25'
413334	Wire-Ring Collars (Both Ends)	20"	25'
450950	Belted-Cuff / Wire-Ring Collars	12"	12'
450951	Belted-Cuff / Wire-Ring Collars	12"	25'
450952	Belted-Cuff / Wire-Ring Collars	16"	25'
450953	Belted-Cuff / Wire-Ring Collars	20"	25'
450954	Belted-Cuff / Wire-Ring Collars	24"	25'

To learn more about Norseman and our gear, contact one of your local Norseman Sales Representatives or visit our website.

CANADA 1.800.268.1918 NORSEMAN.CA
USA 1.844.667.7362 NORSEMANUSA.COM