



NIGHT-LITE™

GR-SERIES LIQUID-COOLED

Model	Kubota Diesel	CAT Diesel
Engine Make	Kubota	CAT
Engine Model	D1005	C1.1
Estimated Engine Prime Power (kW)	6	
Fuel Capacity (gal [L])	63 (238)	
HP @ 1800 RPM	11.6	13.8
Emission Tier	Tier 4 Final	
LED Wattage	350	
Light Output Per Lamp (Lumens) - 350W LED	51,122	
Lumens Total - 350W LED	204,488	
Engine Cooling	Liquid-Cooled	
Operating Time (Hrs) 350W LED	214	195
Estimated LED Life (Hrs)	50,000	
Outlets	Single 120V/20A Duplex GFCI Single 120V/30A RV Single 240V/30A 4 Prong Twistlock	
Max Width (in)	98	
Transport Width (in)	50.5	
Max Height (in)	276	
Transport Height (in)	98.5	
Tongue Out Length (in)	106.5	
Tongue Up Length (in)	86.25	
Operating Temperatures	-40°F* / 120°F	
Shipping Weight (lbs [kg]) (No Fuel)	1,355 (615)	
Net Weight - Dry (lbs [kg])	1,310 (594)	
Net Weight - Wet (lbs [kg])	1,750 (794)	
Number of Units on 48' Flatbed	18	
Number of Units on 53' Flatbed	20	

* Arctic Package Required for -40°F

OPTIONS

Night-Lite™ GR-Series Liquid-Cooled

Available Options at Launch	Kubota Diesel	CAT Diesel
Arctic Package (immersion heater and HD battery)		✓
250W Lights		✓
LED Diffuser Panels		✓
Custom Paint		✓
Telematics (customer supplied, factory lead time)		✓
Galv Tower		✓
Electric Winch		✓
Reversible Coupler 2.5" Lunette Ring (no Bulldog)		✓
Bulldog Hitch (no reversible coupler)		✓

BRIGGS & STRATTON
POST OFFICE BOX 702
MILWAUKEE, WI 53201 USA

Copyright ©2021.
All rights reserved.