


# NIGHT-LITE<sup>TM</sup> V-SERIES®

An ROI-driven solution, the **Night-Lite**<sup>™</sup> **V-Series**<sup>®</sup> is built with the efficiency, durability and performance you demand. This light tower is great for special events, building construction and infrastructure construction. This unit is made with a convenient fuel fill neck for quick refueling allowing you to get back to work fast and stay on top of any job. With up to 542,000 total lumens from four metal halide or LED light fixtures and eco-friendly sized units fitting 20 on a 53ft flatbed trailer, the **Night-Lite V-Series** is perfect for any jobsite.




## **KEY FEATURES**

Night-Lite V-Series



Model	NLV-K1005C	NLV-P11	CAT C.1
Engine Brand / Model	Kubota / D1005	Perkins / 403F-11	Caterpillar / C1.1
Engine Prime Power (kW)**	7	8	8
Fuel Capacity gal (L)	45 (170)	45 (170)	45 (170)
Horsepower (@ 1,800 RPM) ****	11.6	13.8	13.8
Engine Tier	Tier 4 Final	Tier 4 Final	Tier 4 Final
Light Type – Metal Halide			
Metal Halide Wattage (per lamp)	1,250	1,250	1,250
Metal Halide Lumens (per lamp / total)	135,500 / 542,000	135,500 / 542,000	135,500 / 542,000
Operating Time (hrs)*** Using four 1,250 W metal halide light fixtures)	72.6	75	75
Light Type – LED()			
LED Wattage (per lamp)	320	320	320
LED Lumens (per lamp / total)	39,810 / 159,240	39,810 / 159,240	39,810 / 159,240
Dperating Time (hrs)*** Using four 320 W LED light fixtures)	155.2	118.4	118.4
Features			
Outlets	Standard 20 A 120 VAC duplex GFCI / 30 A 240 VAC 4-Wire Twist Lock (NEMA L14-30R) / 30 A 120 VAC RV (NEMA TT-30R)		
Weights & Shipping			
Shipping Weight Ibs (kg)	1,885 (855)	1,885 (855)	1,885 (855)
Gross Vehicle Weight Rating (GVWR) lbs (kg)	2,200 (998)	2,200 (998)	2,200 (998)
Number of Units on 48' Flatbed	18	18	18
Number of Units on 53' Flatbed	20	20	20



\* Balloon light only included in raised dimension – balloon light is removed for transportation. \*\* Prime generator electrical output per Allmand<sup>®</sup> testing. \*\*\* Based on one hour run test full fuel tank consumption. \*\*\*\* All power levels are stated gross horsepower as rated by each engine's manufacturers. Allmand<sup>®</sup> has a policy of continuous product improvement and reserves the right to modify its specifications at any time and without prior notice. See operator's manual or www.allmand.com website for complete warranty details.

#### **Night-Lite V-Series**

**TECHNICAL SPECS** 

## **LIGHT COVERAGE**

## **OPTIONS**

#### **Night-Lite V-Series**



Cold Weather Package Heavy-duty battery 775 CCA @ 0° F

Block heater (120 VAC)



LED Package
(4) LED light fixtures

#### **Coliseum Alternator**

Telematics Package (Customer supplied – consult factory)

**Electric Winch Actuated Light Tower** 

Lockable Battery Disconnect

2" Bulldog coupler with 3" lunette ring for pintle hitch

2" ball coupler with 3" lunette ring for pintle hitch

**Custom Paint** 

**Fuel Level Gauge** 

Fluid Containment System (FCS)

**Galvanized Tower** 



#### LSC with E-Stop Package

- LSC 2.1<sup>™</sup> Light Sequence Commander<sup>®</sup> automatically starts engine at sunset and shuts down engine at sunrise – programmable for user preferences.
- Emergency stop switch on exterior of machine

Allmand

**SP**®

CSA (metal halide or LED)



MA XI-HEAT 🔡 1MBTU 🛥

Airstar LED Balloon Light

## **COMPROMISE NOTHING.**

At Allmand, our sole focus is providing jobsite support equipment to help your customers get the job done. Whenever they need it. Wherever they are. And whatever it takes. What's more, our genuine commitment to you — the highest standard of service and lowest total cost of ownership — is simply unmatched. Choose the equipment that comes with complete confidence that jobsite productivity won't go dark at 2 a.m. **Allmand. Above All.** 

### BRIGGS&STRATTON, LLC

POST OFFICE BOX 702 MILWAUKEE, WI 53201 USA Copyright ©2020. All rights reserved.

www.allmand.com