



NEW & ENHANCED

# FOREMAN<sup>®</sup> 230 Indirect-Fired Portable Heater

- ✓ **Highest BTU** in the class at 230,000 btu/hr
- ✓ **Delivers high CFM** with 12" outlet and 16" inlet combination
- ✓ **Operator-friendly control panel** with:
  - Voltmeter that monitors incoming volts
  - Hour meter that clocks actual runtime (heat mode only)
  - Status and diagnostic lights
- ✓ **Aids fuel efficiency** with options to thermostatically control, recirculate, or run in fan-only vent mode
- ✓ **Quiet operation** at 70 dB or less
- ✓ **One-person portability** with **NEW** telescoping handle
- ✓ **NEW 43-gallon tank** for 10 gallons added capacity & +6 hours of max runtime (oil model only)
- ✓ **Efficient storage** with frame that stands-on-end
- ✓ **Jobsite tough** with indoor/outdoor rating, robust parts and protective frame
- ✓ **Two-year warranty**

**L.B. WHITE LINK<sup>™</sup>** L.B. White LINK<sup>™</sup>  
 Now telematics-enabled to put critical alerts, runtime, location, and more at your fingertips.  
 Learn more at [LBWhite.com/LINK](http://LBWhite.com/LINK).

- Accessories** (Sold Separately)
- Vent Pipe Extension
  - Rain Cap
  - Regulator for DF model only
  - Gas Hose for DF model only
  - Duct (12" or 16" dia.)
  - Thermostat with 25 ft cord
  - Beckett<sup>®</sup> GeniSys Contractor Display Tool



**Control Panel:**

- Volt Meter
- Hour Meter
- Diagnostic Lights



Air recirculation option, 16" dia. duct runs up to 25 ft.



Store on end



One-person portability with **NEW** telescoping handle



**NEW & ENHANCED**

# FOREMAN<sup>®</sup> 230

## Indirect-Fired Portable Heater



FOREMAN <sup>®</sup>		230 DF	230 OIL
BTU/H RATING		230,000	230,000
FUEL TYPE		LP/NG	#1 OR #2 DIESEL
FUEL CONSUMPTION MAX	LP (LBS./HR)	10.6	--
	NG (CU.FT/HR)	230	--
	DIESEL 1 OR 2 (G/HR)	--	1.7
INLET GAS PRESSURE MIN./MAX.	LP (IN W.C.)	7/13.5	--
	NG (IN W.C.)	7/13.5	--
BURNER TYPE		BECKETT <sup>®</sup>	BECKETT <sup>®</sup>
TANK CAPACITY (GALLON)		--	43
BLOWER FAN OUTPUT (CFM)		1900	1900
OUTLET STATIC PRESSURE (IN W.C.)		2.5	2.5
OUTLET DUCT DIAMETER (INCH)		12	12
RECIRCULATION DUCT DIAMETER (INCH)		16	16
MOTOR HORSEPOWER		1/2	1/2
ELECTRICAL SUPPLY (VOLTS/HZ/PHASE)		120/60/1	120/60/1
RUNNING AMPS		9	9
UNIT WEIGHT (LBS)		307	354
UNIT LENGTH (IN)		60.2	60.2
UNIT WIDTH (IN)		26.6	26.6
UNIT HEIGHT (IN)		43.3	43.3
SHIP WEIGHT (LBS)*		421	459
SHIP LENGTH (IN)		64.0	64.0
SHIP WIDTH (IN)		35	35
SHIP HEIGHT (IN)		54	54
LINK <sup>™</sup> CAPABLE		S	S
LINK <sup>™</sup> READY		0	0
THIRD PARTY CERTIFIED TO ANSI Z83.7/CSA 2.14-2017		YES	YES



**TWO YEAR WARRANTY**



S=Standard O=Optional

\* Ships on custom pallet

Heaters ship standard to run at 0-2000 feet.  
To operate at higher altitudes, please note in order process to allow for appropriate deviation.

**CA RESIDENTS:**  
 **WARNING**  
 Cancer and reproductive harm. See [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650  
 (800) 345 7200  
 (608) 783 5691  
 (608) 783 6115, fax  
[www.lbwhite.com](http://www.lbwhite.com)

 **MADE IN USA**  
 OF U.S. & IMPORTED PARTS

© 2021 L.B. White Co.  
 All rights reserved.  
 All specifications are subject to change without notice.