

# BIBI 26-HE



TRACK BASED SCISSOR LIFT

BIBI  
26-HE

Making its North American debut, the BIBI 26HE is the first scissor lift that can both drive and set up on soft and uneven surfaces. Almac in Italy is the global authority when it comes to taking a new path to solve a common problem.

Thanks to the adjustable and unique tracks the unit can go places no other lift can go. Even through a single-door access!

The outrigger system ensures maximum stability and provides safe operation up to 14° rear and 13° front sloping, not to mention a staggering 23° side sloping

With the automatic leveling and inclination control, the operator will always be in a safe position as the unit constantly monitors the operational limits.

With a work height of 26ft the BIBI 26-HE is the safe solution and alternative to ladders and other lift solutions.

Technical data	Bibi 26-HE
Basket capacity	551 lbs (2 persons)
Max working height	25.8 ft
Max height basket floor	19.2 ft
Moving height	13.2 ft
Lateral levelling for moving at heights	-
Powered (Standard)	Gasoline Honda GX270
Powered (option 1)	Gasoline Honda iGX390
Powered (option 2)	Diesel Hatz 1B40
Accelerator	Manual
Undercarriage	Adjustable
Basket leveling	Automatic
Leveling Front	+/- 13°
Leveling Rear	+/- 14°
Side leveling	+/- 23°
Power generator (option)	220V-1kW (iGX390, 1B40)
Electric pump (option)	220V-2.2 kW
Hydraulic commands	Proportional
Direction-Control System	Yes
Easy-Drive System	No
Kit for high speed	max 1.4 mp/h
Ground emergency lowering	Yes
Control of inclination	Automatic
Gradeability	25°
Side slope	21°
Length	84.3"
Width	31,3" ÷ 48,8"
Min. machine height with folded railings	74"
Total weight	3858 lbs
Compliance	EN 280 : 2015



- 26ft work height
- 19ft drive height
- Single door access
- Outriggers with automatic leveling
- Slide-out basket extension
- Adjustable tracks
- All-terrain driving capabilities

ALL DATA REPORTED IN THIS CATALOGUE ARE NOT BINDING. ALMAC SRL RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE.

