



Hand-Arm-Vibrations < 2,4 m/s<sup>2</sup>

### Technical data

Type	CR5 Honda	
Operating weight CECE	lbs.	617
Operating width	in.	22 / 28*
Centrifugal force	lbs.	10,150
Frequency	Hz	75
Engine manufacturer / type	Honda	GX 270 (gas)
Engine power output, max.	HP	8.2
Power output at operating speed	HP at r.p.m	7.0 at 3,000
Working speed (average forward & reverse)	ft/min.	0-66
Dimensions (L x W x H), in.	in.	60 x 22 x 42

\*Operating width with extension plates (optional).

We reserve the right to alter specifications.

## CR5 Honda

### REVERSIBLE SOIL COMPACTOR

The CR5 Honda offers impressive compaction capacity and high operational comfort with the quality you need to handle tough tasks on the job site.

The durable and rugged quality of the CR5 can be seen and felt in details such as the well-built engine protection frame, self-adjusting centrifugal clutch and hydraulic control for infinitely variable forward and reverse travel.

This machine is used for a wide variety of applications. With a compaction force of 10,150 lbs. and weighing only 602 lbs., this machine has excellent running qualities and high gradeability to assure optimum productivity. The low vibration guide bar also minimizes hard-arm vibrations for extra smooth operation.

A long service life and operational reliability are guaranteed with easy access to essential maintenance points making this machine a favorite for rental fleets.

### AREAS OF APPLICATION

trenches or large areas  
landscape/hardscape  
road construction

installing interlocking pavers  
general compaction tasks  
civil engineering

### ADVANTAGES OF CR5 HONDA:

- low hand-arm vibration and lockable guide bar
- all-around encloser and sturdy frame to protect engine
- closed v-belt guard
- flexible working widths thanks to extension plates
- quick and safe loading with hinged lifting eye
- eyelets in console for secure lashing and transport
- infinitely variable hydraulic shifting mechanism used for forward & reverse travel
- hydraulic hoses protected within the guide bar
- unobstructed access to all maintenance points
- self-adjusting centrifugal clutch
- hour meter

### AVAILABLE ACCESSORIES:

Polyurethane pad  
Extension plates (extends to 28")

