



# D210UHJD4PTOW

TIER 4 FINAL \ JOHN DEERE ENGINE \ UTILITY MOUNT COMPRESSOR \ DUAL PRESSURE



210CFM/100PSI & 150PSI



Dependable by design.<sup>™</sup>

## SPECIFICATIONS

### Compressor

#### Model

Rated Delivery
Rated Operating Pressure
Operating Pressure Range
Estimated Weight, Serviced
Dimensions L x W x H (in")

### Engine

Туре	Diesel
Make & Model	John Deere 4045TFC03A Tier 4 Final
Idle Speed	1600 RPM
Fuel Tank Capacity	25 gal (94.6 L)
Horsepower @ rated RPM	74 hp (55.5 kW)
Full Load Speed	2500 RPM

#### **FEATURES**

- 1. Engine Air Filter
- 2. Curbside Fuel Fill
- 3. Compressor Air Filter
- 4. Compressor Oil Filter
- 5. Extended Dipstick
- 6. Fuel/Water Separator
- 7. Engine Oil Filter
- 8. Primary Fuel Filter



#### SPEC CONTROLLER · · · · · ·

- » Digital readouts
- » Complete engine diagnostic tool
- » Measurement converter
- » Multilingual capabilities
- » Waterproof up to six feet

# Sullivan-Palatek, Inc. 1201 West US Highway 20

219.874.2497

sullivan-palatek.com 🖄 info@palatek.com

FEATURES

- » Utility Mount Air Compressor
- » Curbside Controls
- » Large, 108mm Diameter Twin Screw Air End
- » Exclusive Three Year Air End Warranty
- » Automatic 0 to 100% Capacity Control
- » Two Stage Dry Type Air Filter -**External Access**
- » High-Low Selector Switch (PTO must be used in low pressure)
- » Oil Level Sight Gauge
- » John Deere Engine
- » Galvanneal Enclosure
- » Steel Fuel Tank
- » Side by Side Coolers for **Compressor and Engine**
- » Compact Size for Truck Mounting
- » Curbside Fuel Fill & Air Filter Access
- » Noise Level Limited to Maximum of 76 dBA at 7 Meters
- » All Drains End Mounted
- » Automatic Shutdown and **Protection System**
- » Automatic Blowdown Valve
- » Unloaded Starting
- » A Flange PTO (100 psi)

#### CONTROLLER

- » Sullivan-Palatek Electronic Controller (SPEC)
- **Digital Readouts:** » Compressor temperature
- » Discharge Pressure
- » Engine oil pressure
- » Engine temperature
- » Voltmeter
- » Tachometer
- » Fuel level low fuel warning and shutdown
- » Complete engine diagnostic tool
- » Unit converter
- » Multilingual capabilities
- » Waterproof up to six feet

				<u> </u>
·		1	2	
4	6	3	5	
		0		
8			1	
p <del>=</del> 1		0 0		

#### D210UHJD4PTOW

210 CFM (5.9 m <sup>3</sup>/min) 100 psig (6.9 bar) & 150 psig (10.4 Bar) 70-165 psig (4.9 - 11.3 Bar) 2,550 lbs (1,157 kg) 80" x 35" x 57.31"