



# NEW & ENHANCED FOREMAN<sup>®</sup> 750 Indirect-Fired Portable Heater

- ✓ Lightest weight and only one-person portable 750,000 btu/hr indirect-fired heater on the market
- ✓ Reliable CFM with two 12" dia. outlet
- ✓ Quiet operation at 70 dB or less
- ✓ NEW Operator-friendly control panel with:
  - Voltmeter that monitors incoming volts
  - Hour meter that clocks actual runtime (heat mode only)
  - Status and diagnostic lights
- ✓ Loaded with options to aid fuel efficiency including thermostatic control, recirculation mode, and fan-only vent mode
- ✓ NEW 57-gal. backup fuel tank for 15-gal of added capacity and +3 to 4 hours of max runtime (oil model only)
- ✓ NEW remote tank connection that allows for quick switch to backup fuel tank
- ✓ Jobsite tough with indoor/outdoor rating, robust parts and protective frame
- ✓ Efficient storage options with no flat wheels and frame that allows for vertical stacking

**L.B. WHITE LINK** L.B. White LINK<sup>™</sup>  
 Now telematics-enabled to put critical alerts, runtime, location, and more at your fingertips.  
 Learn more at [LBWhite.com/LINK](http://LBWhite.com/LINK).

- Accessories (Sold Separately)**
- Vent Pipe Extension
  - Rain Cap
  - Regulator for DF model only
  - Gas Hose for DF model only
  - Duct (12", 16" and/or 20" dia.)
  - Duct Adapter (Takes 2 x 12" down to 1 x 16")
  - Thermostat with 25 ft cord
  - Beckett<sup>®</sup> GeniSys Contractor Display Tool (For oil model only)
  - Stacking Kit



Two 12" dia. duct up to 100 ft.



One 16" dia. duct up to 100 ft. using duct adapter (sold separately)



One-person portability



Powder-coated protective frame

Single point lifting bale

Thermostatic control option

## Foreman<sup>™</sup> 750 DF



Fork pockets



**NEW** Control Panel:  
• Volt Meter  
• Hour Meter  
• Diagnostic Lights



Easy access rear panel for maintenance and air recirculation option; just add 20" duct



Stackable (kit sold separately)



**NEW & ENHANCED**

# FOREMAN<sup>®</sup> 750

## Indirect-Fired Portable Heater



FOREMAN <sup>®</sup>		750 DF	750 OIL
BTU/H RATING		750,000	750,000
FUEL TYPE		LP, NG	#1 OR #2 DIESEL
FUEL CONSUMPTION MAX	LP (LBS./HR)	34.4	-
	NG (CU.FT/HR)	750.0	-
	DIESEL 1 OR 2 (G/HR)	-	5.4
INLET GAS PRESSURE MIN./MAX.	LP (IN W.C.)	8/13.5	-
	NG (IN W.C.)	8/13.5	-
BURNER TYPE		RIELLO <sup>®</sup>	BECKETT <sup>®</sup>
TANK CAPACITY (GALLON)		-	57 GAL
BLOWER FAN OUTPUT (CFM)		4,280	4,280
OUTLET STATIC PRESSURE (IN W.C.)		2.5	2.5
OUTLET DUCT DIAMETER (INCH)		12X2	12X2
RECIRCULATION DUCT DIAMETER (INCH)		20	20
MOTOR HORSEPOWER		2.0	2.0
ELECTRICAL SUPPLY (VOLTS/HZ/PHASE)		240/60/1	240/60/1
RUNNING AMPS		13.5	13.5
UNIT WEIGHT (LBS)		845	1000
UNIT LENGTH (IN)		94.0	94.0
UNIT WIDTH (IN)		32.0	32.0
UNIT HEIGHT (IN)		53.0	53.0
SHIP WEIGHT (LBS)*		865.0	1021.0
SHIP LENGTH (IN)		101	101
SHIP WIDTH (IN)		39	39
SHIP HEIGHT (IN)		60	60
LINK <sup>™</sup> CAPABLE		S	S
LINK <sup>™</sup> READY OPTION		0	0
THIRD PARTY CERTIFIED TO ANSIZ83.7/GSA 2.14-2017		YES	YES



**TWO YEAR WARRANTY**



S=Standard O=Optional

\*Ships on custom pallet.

Heaters ship standard to run at 0-2000 feet. To operate at higher altitudes, please note in order process to allow for appropriate deviation.

**CA RESIDENTS:**  
 **WARNING**  
 Cancer and reproductive harm. See [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650  
 (800) 345 7200  
 (608) 783 5691  
 (608) 783 6115, fax  
[www.lbwhite.com](http://www.lbwhite.com)

 **MADE IN USA**  
 OF U.S. & IMPORTED PARTS

© 2021 L.B. White Co.  
 All rights reserved.  
 All specifications are subject to change without notice.